



Screw Terminal Blocks

230/ 8 DS

Order Info

reference number (ref. no.)	121308
PU	400
EAN	4028012113866



Type

Type	terminal block
connection type	screw
number of poles	8 pole
colour	natural
wire protection	yes

Electrical Data

rated voltage	450 V
rated current	24 A

Connection Data

rated connecting capacity	2.5 mm ²
cross-sectional area (UL)	22-12 AWG
clamping range	0.5-4.0 mm ²
type of conductor	fine stranded, stranded, solid
stripping length	5.0-5.5 mm
fixing	Screw
clamping units per pole	1
contact screw assembly	0.8 x 4.0 / $\curvearrowright$ 0.5 Nm
mounting hole diameter	2.8 mm
socket diameter	2.40 mm
pin spacing	8.0 mm

Ambient Conditions

T _{max} ambient air (at rated current)	85 °C
T _{min} ambient air (operation)	-40 °C
T _{max} component (operation)	105 °C

Materials

insulator material	PA
contact material	brass

flammability rating acc. to UL 94	V-2
-----------------------------------	-----

Approvals

acc. to EN 60998

acc. to UL

acc. to CSA

Accessories

230 BZ/ 6	191206
-----------	--------

ZEL 110	196420
---------	--------