




## Screw Terminal Blocks

### 230/12 DS

terminal block, 12 pole, insulating material: PA 6, cross-section rating: 2.5 mm<sup>2</sup>, pin spacing: 8.0 mm, wire protector (DS): yes, fixing: screw, voltage rating: 450 V, current rating: 24 A



### Order Info

reference number (ref. no.)	121312
PU	50
EAN	4028012105274

### Type

type	terminal block
number of poles	12 pole
clamping units per pole	1
colour	natural
cross-section rating	2.5 mm <sup>2</sup>
wire protector (DS)	yes

### Technical Data

voltage rating	450 V
current rating	24 A
insulating material	PA 6
contact material	brass
core cross-section min.	0.5 mm <sup>2</sup>
core cross-section max.	2.5 mm <sup>2</sup>
flammability rating	V-2
max. Ambient Temperature Operation	85 °C
type of conductor solid	yes
type of conductor flexible	yes
type of conductor stranded	yes
stripping length	5.0-5.5 mm
Assembly Contact Screw	0.8x4.0 / ⌀ 0.5 Nm
pin spacing	8.0 mm
fixing	screw

### Approvals

acc. to EN 60998

[Download PDF](#)

**acc. to UL** [Download PDF](#)

---

**acc. to CSA** [Download PDF](#)

---

## Accessories

---

**230 BZ/12** 191212

---

**ZEL 110** 196420

---