



## Screw Terminal Blocks

### 1500/12

terminal block, 12 pole, insulating material: PA 6, cross-section rating: 10.0 mm<sup>2</sup>, pin spacing: 13.5 mm, fixing: screw, voltage rating: 500 V, current rating: 57 A



### Order Info

reference number (ref. no.)	127012
PU	25
EAN	4028012100033

### Type

type	terminal block
number of poles	12 pole
clamping units per pole	1
colour	natural
cross-section rating	10.0 mm <sup>2</sup>

### Technical Data

voltage rating	500 V
current rating	57 A
insulating material	PA 6
contact material	brass
core cross-section min.	0.5 mm <sup>2</sup>
core cross-section max.	10.0 mm <sup>2</sup>
flammability rating	V-2
max. Ambient Temperature Operation	85 °C
type of conductor solid	yes
type of conductor flexible	yes
type of conductor stranded	yes
stripping length	8.0-8.5 mm
Assembly Contact Screw	0.8x4.0 / ⌀ 1.2 Nm
pin spacing	13.5 mm
fixing	screw

### Approvals

acc. to EN 60998	<a href="#">Download PDF</a>
acc. to UL	<a href="#">Download PDF</a>

**acc. to CSA**

[Download PDF](#)

---

## Accessories

---

**ZEL 110**

196420

---