



Connectors System AC 162 Low Voltage Connectors

AC 162 STS/ 2 white

plug and socket, 2 pole, voltage rating: 48 V, current rating: 25 A



Order Info

| | |
|-----------------------------|---------------|
| reference number (ref. no.) | 140152 |
| PU | 200 |
| EAN | 4028012102280 |

Type

| | |
|---------------------------------------|---------------------|
| type | plug and socket |
| number of poles | 2 pole |
| clamping units per pole | 1 |
| colour | white |
| cross-section rating | 2.5 mm ² |
| protection against incorrect plugging | yes |
| latch | yes |

Technical Data

| | |
|------------------------------------|---------------------|
| voltage rating | 48 V |
| current rating | 25 A |
| insulating material | PA 6.6 |
| contact material | brass |
| core cross-section min. | 0.5 mm ² |
| core cross-section max. | 2.5 mm ² |
| flammability rating | V-0 |
| max. Ambient Temperature Operation | 70 °C |
| IP code | IP20 |
| type of conductor solid | yes |
| type of conductor flexible | yes |
| type of conductor stranded | yes |
| stripping length | 7.0 mm |
| Assembly Contact Screw | 0.5x3.0 / ⚙ 0.3 Nm |

Accessories

| | |
|----------------------------------|--------|
| XYFAZ 2x0,5 red black 100m Spule | 6099X0 |
|----------------------------------|--------|

XYFAZ 2x0,5 red black 50m Spule

609950
