



Fused Terminal Blocks

503 Si/ 2 DS GW

screwklemme, 2 pole, wire protector (DS): yes, cross-section rating: 2.5 mm², voltage rating: 400 V, current rating: 10 A



Order Info

reference number (ref. no.)	1703G2
PU	300
EAN	4028012117956

Type

type	screwklemme
number of poles	2 pole
clamping units per pole	1
colour	natural
cross-section rating	2.5 mm ²
wire protector (DS)	yes

Technical Data

voltage rating	400 V
current rating	10 A
insulating material	PA 6.6-GW
contact material	brass
core cross-section min.	0.5 mm ²
core cross-section max.	2.5 mm ²
flammability rating	V-2
max. Ambient Temperature Operation	85 °C
type of conductor solid	yes
type of conductor flexible	yes
type of conductor stranded	yes
stripping length	7.0-7.5 mm
Assembly Contact Screw	0.8x4.0 / ⌀ 0.5 Nm
mounting hole diameter	3.1 mm
Type of Conductor Solid External	yes
Type of Conductor Flexible External	yes
Type of Conductor Stranded External	yes
Type of Conductor Solid Internal	yes
Type of Conductor Stranded Internal	yes

Type of Conductor Flexible Internal	yes
--	-----

Approvals

acc. to EN 60127	Download PDF
-------------------------	------------------------------

acc. to UL	Download PDF
-------------------	------------------------------

acc. to CSA	Download PDF
--------------------	------------------------------

Accessories

ZEL 110	196420
----------------	--------

ABK 503/ 2 GW	193812
----------------------	--------