



Screwless Connectors  
Luminaire Connectors

LK 980-01/ 3 SK BD N PE L

terminal block, 3 pole, insulating material: PA 6.6, fixing: screw, PE terminal: SK, printing: N ⊕ L, voltage rating: 450 V, current rating: 24.0 A, cross-section rating: 2.5 mm<sup>2</sup>



Order Info

reference number (ref. no.)	21756
PU	500
EAN	4028012112890

Type

type	terminal block
number of poles	3 pole
clamping units per pole	2
colour	white
cross-section rating	2.5 mm <sup>2</sup>
connection type	screwless
printing	N ⊕ L

Technical Data

voltage rating	450 V
current rating	24.0 A
insulating material	PA 6.6
contact material	Spring Steel, Copper
flammability rating	V-2
max. Ambient Temperature Operation	85 °C
stripping length	8.0-9.0 mm
internal core cross-section max.	1.5 / 2.5 mm <sup>2</sup>
external core cross-section min.	0.5 mm <sup>2</sup>
external core cross-section max.	2.5 mm <sup>2</sup>
fixing	screw
internal core cross-section min.	0.5 mm <sup>2</sup>
Type of Conductor Solid External	yes
Type of Conductor Flexible External	yes
Type of Conductor Solid Internal	yes
Type of Conductor Stranded Internal	yes
PE terminal	SK

## Approvals

**acc. to EN 60998**

[Download PDF](#)

**acc. to UL**

[Download PDF](#)

## Accessories

**WKZ 980-01**

999041

**ZEL 110**

196420

**ZEL 900**

196423