



Circular Terminal Blocks IP68  
Circular Terminal Blocks AC 179 kompakt  
**AC 179 SK/ 4 SL**



terminal block, 4 pole, voltage rating: 450 V, current rating: 17.5 A, cross-section rating: 4.0 mm<sup>2</sup>

### Order Info

<b>reference number (ref. no.)</b>	741064D3
<b>PU</b>	200
<b>EAN</b>	4028012167197

### Type

<b>type</b>	terminal block
<b>number of poles</b>	4 pole
<b>clamping units per pole</b>	1
<b>colour</b>	black
<b>cross-section rating</b>	4.0 mm <sup>2</sup>

### Technical Data

<b>voltage rating</b>	450 V
<b>current rating</b>	17.5 A
<b>insulating material</b>	PA 6.6
<b>contact material</b>	brass
<b>core cross-section min.</b>	0.75 mm <sup>2</sup>
<b>core cross-section max.</b>	4.0 mm <sup>2</sup>
<b>flammability rating</b>	V-2
<b>max. Ambient Temperature Operation</b>	85 °C
<b>IP code</b>	IP68
<b>type of conductor solid</b>	yes
<b>type of conductor flexible</b>	yes
<b>type of conductor stranded</b>	yes
<b>stripping length</b>	6.0 mm
<b>dismantling length</b>	20.0 mm
<b>Assembly Contact Screw</b>	0.5x3.0 / ⚙ 0.5 Nm
<b>strain relief assembly</b>	⚙ 2.5 Nm
<b>cable diameter min.</b>	7.0 mm
<b>cable diameter max.</b>	12.0 mm

## Accessories

<b>AC 179 RVK/ 4 M20</b>	749564
<b>DR 14 1x5,5x11</b>	729007
<b>DR 14 1x3,5</b>	729008
<b>DR 14 1x7,0</b>	729001
<b>DR 14 2x3,0</b>	729003
<b>DR 14 2x5,0</b>	729004
<b>DR 14 3x3,0</b>	729005
<b>DR 14 4x3,0</b>	729006
<b>DR 14 RH</b>	729002
<b>DR 14 GS</b>	729010