



# TKS 10/3 OG

17046.3



Transformer terminal, Screw connection, Mounting type: Custom profile, Rated cross-section: 10 mm<sup>2</sup>, Width: 23.75 mm, Colour: Orange

## Commercial

### General

Colour: Orange

Country of origin: CZ

Customs number: 85369010

GTIN (EAN): 4044211149819

Packaging unit: 20

Product description: Transformer terminal

Quantity unit: PC

Unit of weight: G

Weight per piece (including packaging): 45.4g

Weight per piece (not including packaging): 45g

---

## Technical

---

### Dimensions

---

Height: 39.5mm

Length: 37.5mm

Width: 33.75mm

---

### Ratings

---

Contamination degree: 3

Maximum power dissipation for nominal condition: 5.47W

Overvoltage category: III

Rated cross-section: 10mm<sup>2</sup>

Rated current: 57A

Rated impulse voltage: 8kV

Rated voltage: 800V

---

### Connection data

---

Connection principle: Screw connection

Connections: 3

Screw head: Slotted

Screw threading: M 4

Stripping length: 14mm

Tightening torque, max.: 2Nm

Tightening torque, min.: 1.2Nm

Wire cross-section AWG, max.: 6

Wire cross-section AWG, min.: 24

Wire cross-section single core (rigid)/stranded, max.: 16mm<sup>2</sup>

Wire cross-section single-core (rigid) / stranded, min.: 0.2mm<sup>2</sup>

Wire cross-section stranded with wire-end ferrules, max.: 10mm<sup>2</sup>

Wire cross-section stranded with wire-end ferrules, min.: 0.2mm<sup>2</sup>

Wire cross-section stranded, max.: 16mm<sup>2</sup>

Wire cross-section stranded, min.: 0.2mm<sup>2</sup>

---

### Further technical data

---

Gauge plug acc. to EN 60 947-1: B6

---

Mounting type: Custom profile

---

## Materials

Flammability class UL 94: V-0

Insulation housing: Polyamide 6.6

Working temperature, max.: 120°C

Working temperature, min.: -40°C

---

## Approvals

---

### Standards and regulations

---

EAC approval: TR ZU 004/2011

EAC approval granted: ✓

### KEMA KEUR approval

---

KEMA KEUR approval: EN 60947-7-1:2009

KEMA KEUR approval granted: ✓

KEMA rated current: 57A

KEMA rated impulse voltage (fuse holder without electrical components): 8kV

KEMA rated voltage: 800V

KEMA torque, max.: 2Nm

KEMA torque, min.: 1.2Nm

KEMA wire cross-section single core (rigid), min.: 0.2mm<sup>2</sup>

KEMA wire cross-section single-core (rigid), max.: 16mm<sup>2</sup>

KEMA wire cross-section stranded, max.: 10mm<sup>2</sup>

KEMA wire cross-section stranded, min.: 0.2mm<sup>2</sup>

---

### UL Recognized

---

UL File Number: E95701

UL Recognized: 1

UL Usegroup B: rated current: 65A

UL Usegroup B: rated voltage: 600V

UL Usegroup C: rated current: 65A

UL Usegroup C: rated voltage: 600V

UL approval: UL 1059

UL factory wiring: ✓

UL field wiring: ✓

UL torque, max.: 17.7Lb In.

---

UL torque, min.: 10.6Lb In.

UL wire cross-section single-core (rigid) AWG, max.: 6

UL wire cross-section single-core (rigid) AWG, min.: 24

UL wire cross-section stranded AWG, max.: 6

UL wire cross-section stranded AWG, min.: 24

UL wire material: Cu

### **CSA approval**

CSA Usegroup B: rated current: 65A

CSA Usegroup B: rated voltage: 600V

CSA Usegroup C: rated current: 65A

CSA Usegroup C: rated voltage: 600V

CSA approval: C22.2 No 158

CSA approval granted: ✓

CSA torque, max.: 2Nm

CSA torque, min.: 1.2Nm

CSA wire cross-section AWG, max.: 6

CSA wire cross-section AWG, min.: 24

### **CSAus approval**

CSAus Usegroup B: rated current: 65A

CSAus Usegroup B: rated voltage: 600V

CSAus Usegroup C: rated current: 65A

CSAus Usegroup C: rated voltage: 600V

CSAus approval: UL 1059

CSAus approval granted: ✓

CSAus torque, max.: 2Nm

CSAus torque, min.: 1.2Nm

CSAus wire cross-section AWG, max.: 6

CSAus wire cross-section AWG, min.: 24

## **Environment**

---

### **Environmental Product Compliance**

---

EU-POP Conform: Yes

PROP 65 Conform: Yes

REACH Candidate Substance Note: No

REACH Conform: Yes

---

REACH Reference date: 2026-02-04

RoHS Conform: Yes

TSCA Conform: Yes

---

## Accessories

---

### Quick marking

---



**PMC SB 7,5/40 WH**

9326.7

---



**PMC SB 7,5/40 So WH**

3327.7

---

### Screwdriver

---



**SDB 0,6x3,5**

1086.0

---