Product Data Sheet

One27 Male high-profile,
Part No. 403-54012-51





Illustration similar

Parallel | Perpendicular | SMT | High Density | Rugged

- 12 pins
- unmated stacking height: 4.85 mm
- for board-to-board distances from 11.1 to 20.0 mm
- SMT
- pitch 1.27 mm
- Performance level 1

» to product on www.ept.de

» to product group One27

ept GmbH | Bergwerkstr. 50 | 86971 Peiting | Tel. +49 (0) 8861 / 25 01 0 | Fax +49 (0) 8861 / 55 07 | sales@ept.de | **www.ept.de**

Product Data Sheet

One27 Male high-profile, Part No. 403-54012-51

Technical Specifications

Basics

No. of Contacts	12
Termination Technology	SMT
Board-to-Board Distance	11.1 mm to 20.0 mm
Operating Temperature Range	-55°C to + 125°C

Material

Insulator Material	LCP, UL 94 V-0
CTI value *IEC 60112*	175
Contact Material	Copper alloy
Plating	Au over NiP over Ni
Termination area	Sn over Ni

Mechanical

Pitch	1.27 mm
Mating Force per Pin	≤ 0.5 N
Separating Force per Pin	≥ 0.1 N
Durability *IEC 60512-9-1*	Performance level 1: 500 mating cycles
Coplanarity	≤ 0.1 mm
Vibration, sinusoidal *IEC 60512-6-4*	10 - 2000 Hz, 20g
Contact mating problems if vibrations occur, sinusoidal *IEC 60512-2-5*	≤ 1 µs
Shock, semi-sinusoidal *IEC 60512-6-3*	50g, 11 ms
Contact mating problems if shock occur, semi-sinusoidal *IEC 60512-2-5*	≤ 1 µs

Electrical

Operational Current *IEC 60512-5-2*	3.1 A at 20°C (4 of 50 pins) 1.4 A at 20°C (50 of 50 pins)
Contact Resistance *IEC 60512-2-1*	≤ 25 mΩ
Clearance and Creepage	min. 0.4 mm
Insulation Resistance *IEC 60512-3-1*	≥ 10 GΩ
Test Voltage *IEC 60512-4-1*	500 VAC

ept GmbH | Bergwerkstr. 50 | 86971 Peiting | Tel. +49 (0) 8861 / 25 01 0 | Fax +49 (0) 8861 / 55 07 | sales@ept.de | **www.ept.de**

Product Data Sheet

One27 Male high-profile, Part No. 403-54012-51

Technical Specifications

Processing

Soldering Temperature *JEDEC J-STD-020E*	20 - 40 s at 260°C
MSL *JEDEC J-STD-020E*	1
Assembly	Pick and Place

Approval / Compliance

UL file	E130314
Environment	RoHS compliant

ept GmbH | Bergwerkstr. 50 | 86971 Peiting | Tel. +49 (0) 8861 / 25 01 0 | Fax +49 (0) 8861 / 55 07 | sales@ept.de | **www.ept.de**

Derating Diagram



ept GmbH | Bergwerkstr. 50 | 86971 Peiting | Tel. +49 (0) 8861 / 25 01 0 | Fax +49 (0) 8861 / 55 07 | sales@ept.de | **www.ept.de**

Modifications

Available on request

- different number of pins
- other performance level

Drawings

Component data in 2D and 3D format you can download here:

» PDF » 3D IGES » 3D STEP » 3D PDF